

## Safety Data Sheet according to HPR, Schedule 1

Printing date 05/13/2021

Reviewed on 04/12/2021

### 1 Identification

- **Product identifier:** BP-40-1G, BP-40-5G
- **Trade name:** **BP-40 Universal Tape Butyl Primer**
- **Item number(s):** BP-40-1G, BP-40-5G
- **SDS Number:** 407
- **Application of the substance / the mixture** Primer for water-proofing applications
- **Manufacturer/Supplier:**  
 USA ADDRESS:  
 KEMPER SYSTEM AMERICA, INC.  
 1200 NORTH AMERICA DR,  
 WEST SENECA, NY 14224  
 PH (716) 558-2971  
  
 CANADIAN ADDRESS:  
 ASTARAS CANADA, INC.  
 4-7075 EDWARDS BLVD  
 MISSISSAUGA, ONTARIO, L5S 1Z2  
 PH (905) 624-5463
- **Information department:**  
 Tel: (716) 712-9931  
 www.kempersystem.net
- **Emergency telephone number:**  
 ChemTrec (800) 424-9300 / 1-(703)-741-5970  
 Canada only: CANUTEC (Call collect) (613) 996-6666

### 2 Hazard identification

· **Classification of the substance or mixture:**



GHS02 Flame

Flammable Liquids - Category 2

H225 Highly flammable liquid and vapour.



GHS08 Health hazard

Reproductive Toxicity - Category 2

H361 Suspected of damaging fertility or the unborn child.

Specific Target Organ Toxicity - Repeated Exposure - Category 2 H373 May cause damage to the central nervous system, the kidneys and the liver through prolonged or repeated exposure.

Aspiration Hazard - Category 1

H304 May be fatal if swallowed and enters airways.



GHS07

Skin Irritation - Category 2

H315 Causes skin irritation.

Eye Irritation - Category 2A

H319 Causes serious eye irritation.

(Contd. on page 2)

# Safety Data Sheet

## according to HPR, Schedule 1

Printing date 05/13/2021

Reviewed on 04/12/2021

**Trade name:** BP-40 Universal Tape Butyl Primer

(Contd. of page 1)

Specific Target Organ Toxicity - Single Exposure - H336 May cause drowsiness or dizziness.  
Category 3

· **Label elements**

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Signal word:** Danger

· **Hazard-determining components of labeling:**

Solvent naphtha (petroleum), light aliph.

Benzene, Methyl-

acetone

benzene

· **Hazard statements:**

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H361 Suspected of damaging fertility or the unborn child.

H336 May cause drowsiness or dizziness.

H373 May cause damage to the central nervous system, the kidneys and the liver through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.

· **Precautionary statements:**

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.  
No smoking.

P233 Keep container tightly closed.

P240 Ground and bond container and receiving equipment.

P241 Use explosion-proof [electrical/ventilating/lighting] equipment.

P243 Take actions to prevent static discharges.

P260 Do not breathe mist/vapors/spray.

P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 If swallowed: Immediately call a doctor.

P331 Do NOT induce vomiting.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

P304+P312 IF INHALED: Call a doctor if you feel unwell.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P314 Get medical advice/attention if you feel unwell.

P332+P313 If skin irritation occurs: Get medical advice/attention.

P362+P364 Take off contaminated clothing and wash it before reuse.

P337+P313 If eye irritation persists: Get medical advice/attention.

P370+P378 In case of fire: Use for extinction: CO<sub>2</sub>, sand, extinguishing powder.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 3)

# Safety Data Sheet

## according to HPR, Schedule 1


Printing date 05/13/2021

Reviewed on 04/12/2021

**Trade name:** BP-40 Universal Tape Butyl Primer

(Contd. of page 2)

- **Information pertaining to particular dangers for man and environment:**
- **NFPA ratings (scale 0 - 4):**



Health = 2  
Fire = 3  
Reactivity = 0

### 3 Composition/Information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

64742-89-8	Solvent naphtha (petroleum), light aliph.	15-40% w/w *
67-64-1	acetone	10-30% w/w *
108-88-3	Benzene, Methyl-	10-30% w/w *

\* Actual concentration ranges are withheld as a trade secret.

### 4 First-aid measures

- **After inhalation:**  
If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms: Call a poison center/doctor.
- **After skin contact:**  
Wash with plenty of soap and water. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention.
- **After eye contact:**  
Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing. If eye irritation persists get medical advice/attention.
- **After swallowing:** Do not induce vomiting, Immediately call a poison center/ doctor.
- **Most important symptoms and effects, both acute and delayed:**  
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed:**  
No further relevant information available.

### 5 Fire-fighting measures

- **Suitable extinguishing agents:** CO<sub>2</sub>, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture:** No further relevant information available.
- **Protective equipment:** No special measures required.

### 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures:**  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**  
Do not allow product to reach sewage system or any water course.

(Contd. on page 4)

CA

# Safety Data Sheet

## according to HPR, Schedule 1

Printing date 05/13/2021

Reviewed on 04/12/2021

**Trade name:** BP-40 Universal Tape Butyl Primer

(Contd. of page 3)

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· **Reference to other sections:**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## 7 Handling and storage

· **Handling**

· **Precautions for safe handling:**

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· **Information about protection against explosions and fires:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

· **Storage**

· **Requirements to be met by storerooms and receptacles:** Store in a cool location.

· **Information about storage in one common storage facility:** Not required.

· **Further information about storage conditions:**

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· **Specific end use(s):** No further relevant information available.

## 8 Exposure controls/ Personal protection

· **Additional information about design of technical systems:** No further data; see item 7.

· **Components with limit values that require monitoring at the workplace:**

**67-64-1 acetone**

EL (Canada) Short-term value: 500 ppm

Long-term value: 250 ppm

EV (Canada) Short-term value: 750 ppm

Long-term value: 500 ppm

PEL (USA) Long-term value: 2400 mg/m<sup>3</sup>, 1000 ppm

REL (USA) Long-term value: 590 mg/m<sup>3</sup>, 250 ppm

TLV (USA) Short-term value: 1187 mg/m<sup>3</sup>, 500 ppm

Long-term value: 594 mg/m<sup>3</sup>, 250 ppm

BEI

**108-88-3 Benzene, Methyl-**

EL (Canada) Long-term value: 20 ppm

R

EV (Canada) Long-term value: 20 ppm

PEL (USA) Long-term value: 200 ppm

Ceiling limit value: 300; 500\* ppm

\*10-min peak per 8-hr shift

(Contd. on page 5)

# Safety Data Sheet

## according to HPR, Schedule 1

Printing date 05/13/2021

Reviewed on 04/12/2021

**Trade name:** BP-40 Universal Tape Butyl Primer

(Contd. of page 4)

REL (USA)	Short-term value: 560 mg/m <sup>3</sup> , 150 ppm Long-term value: 375 mg/m <sup>3</sup> , 100 ppm
TLV (USA)	Long-term value: 75 mg/m <sup>3</sup> , 20 ppm BEI

· **Ingredients with biological limit values:**

**67-64-1 acetone**

BEI (USA)	50 mg/L Medium: urine Time: end of shift Parameter: Acetone (nonspecific)
-----------	--

**108-88-3 Benzene, Methyl-**

BEI (USA)	0.02 mg/L Medium: blood Time: prior to last shift of workweek Parameter: Toluene
	0.03 mg/L Medium: urine Time: end of shift Parameter: Toluene
	0.3 mg/g creatinine Medium: urine Time: end of shift Parameter: o-Cresol with hydrolysis (background)

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Personal protective equipment**

· **General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Avoid contact with the eyes and skin.

· **Breathing equipment:**

- In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
- Use suitable respiratory protective device in case of insufficient ventilation.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· **Material of gloves:** Nitrile

· **Eye protection:**



Tightly sealed goggles

CA

(Contd. on page 6)

# Safety Data Sheet

## according to HPR, Schedule 1

Printing date 05/13/2021

Reviewed on 04/12/2021

**Trade name:** BP-40 Universal Tape Butyl Primer

(Contd. of page 5)

### 9 Physical and chemical properties

· <b>Form:</b>	Liquid
· <b>Color:</b>	White
· <b>Odor:</b>	Like ketone
· <b>Odor threshold:</b>	Not determined.
· <b>pH-value:</b>	Not determined.
· <b>Change in condition</b>	
<b>Melting point/Melting range:</b>	Undetermined.
<b>Boiling point/Boiling range:</b>	56.5 °C
· <b>Flash point:</b>	<5 °C
· <b>Flammability (solid, gaseous):</b>	Not applicable.
· <b>Ignition temperature:</b>	465 °C
· <b>Decomposition temperature:</b>	Not determined.
· <b>Auto igniting:</b>	Product is not selfigniting.
· <b>Danger of explosion:</b>	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· <b>Explosion limits</b>	
<b>Lower:</b>	1.2 Vol %
<b>Upper:</b>	13.0 Vol %
· <b>Vapor pressure at 20 °C:</b>	233 hPa
· <b>Density at 20 °C:</b>	0.815 g/cm <sup>3</sup>
· <b>Relative density:</b>	Not determined.
· <b>Vapor density at 20 °C:</b>	3.3 g/cm <sup>3</sup>
· <b>Evaporation rate at 20 °C:</b>	11.6 BA=1
· <b>Solubility in / Miscibility with</b>	
<b>Water:</b>	Not miscible or difficult to mix.
· <b>Partition coefficient (n-octanol/water):</b>	Not determined.
· <b>Viscosity:</b>	
<b>Dynamic:</b>	Not determined.
<b>Kinematic:</b>	Not determined.
· <b>Solvent content:</b>	
<b>VOC content:</b>	341 g/l
· <b>Other information</b>	No further relevant information available.

### 10 Stability and reactivity

- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used according to specifications.
- **Possibility of hazardous reactions:** No dangerous reactions known.
- **Conditions to avoid:** No further relevant information available.
- **Incompatible materials:** No further relevant information available.

(Contd. on page 7)

CA

# Safety Data Sheet

## according to HPR, Schedule 1

Printing date 05/13/2021

Reviewed on 04/12/2021

**Trade name:** BP-40 Universal Tape Butyl Primer

(Contd. of page 6)

- **Hazardous decomposition products:** No dangerous decomposition products known.

### 11 Toxicological information

- **Information on toxicological effects:**

- **Acute toxicity**

- **LD/LC50 values that are relevant for classification:**

#### 108-88-3 Benzene, Methyl-

Oral	LD50	5000 mg/kg (rat)
Dermal	LD50	12124 mg/kg (rabbit)
Inhalative	LC50/4 h	5320 mg/l (mouse)

- **Specific symptoms in biological assay:** No further relevant information available.

- **Primary irritant effect**

- **on the skin:** Irritant to skin and mucous membranes.

- **on the eye:** Irritating effect.

- **Sensitization:** No sensitizing effects known.

- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

108-88-3	Benzene, Methyl-	3
71-43-2	benzene	1

- **NTP (National Toxicology Program)**

71-43-2	benzene	K
---------	---------	---

### 12 Ecological information

- **Aquatic toxicity:** No further relevant information available.

- **Persistence and degradability:** No further relevant information available.

- **Behavior in environmental systems**

- **Bioaccumulative potential:** No further relevant information available.

- **Mobility in soil:** No further relevant information available.

- **Additional ecological information**

- **General notes:**

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- **Other adverse effects:** No further relevant information available.

### 13 Disposal considerations

- **Waste treatment methods**

- **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 8)

# Safety Data Sheet

## according to HPR, Schedule 1

Printing date 05/13/2021

Reviewed on 04/12/2021

**Trade name:** BP-40 Universal Tape Butyl Primer

(Contd. of page 7)

· **Uncleaned packagings**

· **Recommendation:**

Place in a sealed container and label as waste. Place in a safe area, and comply with all federal, state, provincial and local regulations for disposal.

### 14 Transport information

· **UN-Number**

· **DOT/TDG, ADR, IMDG, IATA** UN1263

· **UN proper shipping name**

· **DOT/TDG** Paint  
 · **ADR** 1263 Paint  
 · **IMDG, IATA** PAINT

· **Transport hazard class(es)**

· **DOT/TDG (Transport dangerous goods):**



· **Class** 3 Flammable liquids  
 · **Label** 3

· **ADR, IMDG, IATA**



· **Class** 3 Flammable liquids  
 · **Label** 3

· **Packing group**

· **DOT/TDG, ADR, IMDG, IATA** II

· **Environmental hazards:**

Not applicable.

· **Special precautions for user:**

Warning: Flammable liquids

· **Hazard identification number (Kemler code):** 33

· **EMS Number:** F-E, S-E

· **Stowage Category** B

· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code:**

Not applicable.

· **Transport/Additional information:**

· **DOT/TDG**

· **Quantity limitations**

On passenger aircraft/rail: 5 L  
 On cargo aircraft only: 60 L

(Contd. on page 9)

CA



# Safety Data Sheet

## according to HPR, Schedule 1

Printing date 05/13/2021

Reviewed on 04/12/2021

**Trade name:** BP-40 Universal Tape Butyl Primer

(Contd. of page 8)

· <b>ADR</b>	
· <b>Excepted quantities (EQ)</b>	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· <b>IMDG</b>	
· <b>Limited quantities (LQ)</b>	5L
· <b>Excepted quantities (EQ)</b>	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· <b>UN "Model Regulation":</b>	UN 1263 PAINT, 3, II

### 15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**  
No further relevant information available.

- **Sara**

- **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

- **Section 313 (Specific toxic chemical listings):**

108-88-3 Benzene, Methyl-

71-43-2 benzene

- **TSCA (Toxic Substances Control Act):**

All ingredients are listed or exempted

- **Proposition 65**

- **Chemicals known to cause cancer:**

71-43-2 benzene

- **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

- **Chemicals known to cause reproductive toxicity for males:**

71-43-2 benzene

- **Chemicals known to cause developmental toxicity:**

108-88-3 Benzene, Methyl-

71-43-2 benzene

- **Canadian substance listings**

- **Canadian Domestic Substances List (DSL/NDSL):**

All ingredients are listed.

- **Canadian Ingredient Disclosure list (limit 0.1%):**

None of the ingredients is listed.

- **Canadian Ingredient Disclosure list (limit 1%):**

67-64-1 acetone

108-88-3 Benzene, Methyl-

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 10)

# Safety Data Sheet

## according to HPR, Schedule 1

Printing date 05/13/2021

Reviewed on 04/12/2021

**Trade name:** BP-40 Universal Tape Butyl Primer

(Contd. of page 9)

· **Hazard pictograms**



GHS02 GHS07 GHS08

· **Signal word** Danger

· **Hazard-determining components of labeling:**

Solvent naphtha (petroleum), light aliph.  
Benzene, Methyl-  
acetone  
benzene

· **Hazard statements**

H225 Highly flammable liquid and vapour.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H361 Suspected of damaging fertility or the unborn child.  
H336 May cause drowsiness or dizziness.  
H373 May cause damage to the central nervous system, the kidneys and the liver through prolonged or repeated exposure.  
H304 May be fatal if swallowed and enters airways.

## 16 Other information

This SDS format meets ANSI Z400.1-2010, OSHA 1910.1200 and WHMIS requirements. Kemper System America, Inc. provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product. Product use and conditions of use are beyond the control of Kemper System America, Inc. Warranty of materials is limited to test results of product performance as detailed in certificates of compliance. Interpretation of test results is the responsibility of end-user. No other warranties, expressed or implied, are made. Kemper System America, Inc is an ISO 9001:2015 and ISO 14001:2015 registered company.

· **Department issuing SDS:** Product safety department

· **Contact:**

· **Date of the latest revision of the safety data sheet** 05/13/2021 / -

· **Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods  
DOT: US Department of Transportation  
IATA: International Air Transport Association  
EINECS: European Inventory of Existing Commercial Chemical Substances  
ELINCS: European List of Notified Chemical Substances  
CAS: Chemical Abstracts Service (division of the American Chemical Society)  
NFPA: National Fire Protection Association (USA)  
VOC: Volatile Organic Compounds (USA, EU)  
LC50: Lethal concentration, 50 percent  
LD50: Lethal dose, 50 percent